Chicago Pneumatic







- ✓ Durable 1" Impact Wrench
- ✓ High Torque



Automotive & Maintenance

People. Passion. Performance.

JRABLE & HIGH TORQUE

Powerful

2140 ft lbs 2900 Nm of maximum torque in reverse

DURABLE

Closed reinforced rocking dog clutch

Applications

- Heavy vehicle tire changing
- General mechanical works
- Manufacturing equipment maintenance

EXCELLENT CONTROL

Full teasing trigger



SHOCK ABSORBING

Rubber bumper protecting both applications and tool (included)

USEFUL

Forward/Reverse regulator with 3 positions power setting in both directions

COMFORT

Angled down exhaust blows air away from the operator

GREAT HANDLING

Ergonomic handle with variable positions

Model	Part Number	Impact Mechanism	Anvil	Free Speed	Working Torque		Max Torque		Weight				Avg. Air Con- sumption		Air Cons.@ Load		Sound Pressure	Sound Power	Vibration
			in	RPM	ft.lbs	Nm	ft.lbs	Nm	lbs	kg	in	mm	cfm	l/s	cfm	l/s	dB(A)	dB(A)	m/s²(k)
CP7782	894 107 7820	Rocking dog	Short	5160	440- 1850	600 - 2500	2140	2900	22.2	10.1	14.7	370	10	4.8	40.7	19.2	100	111	6.5 (1.6)
CP7782-6	894 107 7826	Rocking dog	6"	5160	440- 1850	600 - 2500	2140	2900	25.5	11.6	20.4	520	10	4.8	40.7	19.2	100	111	6.5 (1.6)
CP7782-SP6	894 107 7821	Rocking dog	#5 6"	5160	440- 1850	600 - 2500	2140	2900	25.5	11.6	20.4	520	10	4.8	40.7	19.2	100	111	6.5 (1.6)



Chicago Pneumatic also offers a large range of accessories to optimize your air tools durability and performance:

Check www.cp.com website for more information.





